



## NA2MP

3 pole XLR male – Mono 1/4" plug (tip, sleeve contact)

Wired according to IEC 268-12:

Pin 2: signal

Pin 1 and 3: connected to ground

### Features & Benefits

- Versatile, pre-wired and ready to use adapters to reliably interlock various connector systems
- Professional look and compact space saving design, based on the X Series (XLR worldwide accepted standard)
- Rugged diecast shell for best reliability.

**Technical Information**

Product	
<b>Title</b>	NA2MP
<b>Connection Type</b>	Adapter

Electrical	
<b>Contact resistance</b>	≤ 3 mΩ (XLR)
<b>Contact resistance</b>	≤ 6 mΩ
<b>Dielectric strength</b>	1.5 kV dc / > 1 kVdc (XLR/Plug)
<b>Insulation resistance</b>	> 2 GΩ

Mechanical	
<b>Wiresize</b>	
<b>Wiring</b>	according to IEC 268-12 pin 2 = signal, pin 1 and 3 connected to ground
<b>Locking device</b>	Latch lock

Material	
<b>Contact plating</b>	2 μm Ag over 2 μm Ni
<b>Contacts</b>	Brass (CuZn39Pb3) (plug)
<b>Insert</b>	Polyamide (PA 6.6 30 % GR)
<b>Shell</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell plating</b>	gal Cu/Ni

Environmental	
<b>Temperature range</b>	-20 °C to +65 °C