

VMBEL1-PF datasheet

Edge Lit control module with 1 touch key
frosted pure white



Features

- pure white edition (also available in black)
- frosted glass edition (also available in glossy glass)
- configurable by using the Velbus PC interface (VMB1USB or VMBRSUSB) and the free VELBUSLINK program
- feedback/mood lights with RGBW side LEDs (adjustable light intensity and RGB colour or warm white by using VELBUSLINK)
- the light intensity and colour of the feedback and/or mood lights are independently adjustable per side
- adjustable button response time (0, 1, 2 or 3 seconds)
- detection of short or long button press
- configurable multi-channel operation on each push button, the next channel is selected at each press (up to 8 channels)
- configurable dual channel push button, a different channel is selected depending on the length of the push (short or long push)
- extensive day, week and year programs plus a built-in astronomical clock (sunrise and sunset timing) are included to operate push buttons automatically
- integrated temperature sensor to control the heating and air conditioning (only usable when side LEDs are turned off)
- LED-indication for supply voltage and data (backside)
- uses one address for all push buttons and one for the thermostat function (optional) (configurable by using VELBUSLINK)

Protocol manuals for developers: available for download at
<https://github.com/velbus>

VELBUS • VMBEL1-PF

Legen Heirweg 33 • 9890 Gavere • Belgium
velbus.eu

VMBEL1-PF datasheet

Edge Lit control module with 1 touch key
frosted pure white



Specifications

- not suitable for installation on electrically conductive surfaces (eg. metal), or nearby sources of electromagnetic disturbances
- mounting frame included (screw / clamp)

| | |
|--------------------|---|
| touch technology | SMSC RightTouch® |
| material | safety glass |
| supply voltage | 15±3 VDC |
| possible addresses | 250 |
| programming steps | max. 66 |
| dimensions | 86 x 86 x 11 mm 4 mm glass + 7 mm to wall installation depth: 28 mm including the connector |
| temperature range | -10°C to +40°C |
| power consumption | when side LEDs are off: 25 mA when side LEDs are full brightness: 110 mA |

Protocol manuals for developers: available for download at <https://github.com/velbus>

VELBUS • VMBEL1-PF
Legen Heirweg 33 • 9890 Gavere • Belgium
velbus.eu